

# S3450D

3-1/2" Series

## Low Profile Adjustable Shower

### SPECIFICATIONS

TRIM	Powder coat painted or plated die-formed steel. Different finishes available. Painted finishes available with Marine Grade option.	
LAMPS (maximum wattage)	<b>GU10 LED</b> 9.8W <b>MR16 LED GU 5.3</b> 11.5W <b>PAR16 LED</b> 8W	<b>GU10</b> 50W <b>MR16 GU 5.3</b> 20-42W
LENS	<b>Standard: Frosted lens</b> Available: Clear lens (C), Frosted with clear center lens (FC) To order, place the lens code after the trim code. Ex.: S3450DFC-01	
CEILING CUTOUT	Ø 3-5/8" (92 mm)	
CERTIFICATION	<ul style="list-style-type: none"> <li>cULus <b>E343977</b> for <b>wet locations</b> (for GU10, MR16 and PAR16 LED lamps)</li> <li>cULus <b>E174023</b> for <b>wet locations</b> (for MR16, GU10 halogen lamps)</li> </ul>	
WARRANTY	1 year for standard finishes, 2 years on "Marine Grade" finishes.	

### COMPATIBLE HOUSINGS

	IC Air Tight Remodel Housing	IC Air Tight New Construction Housing
LED	<b>GU10 LED</b> 9.8W IT3000T-LED  <b>MR16 LED GU 5.3</b> 11.5W IT3000CE-LED IT3000E-LED  <b>PAR16 LED</b> 8W CA3000-LED	<b>GU10 LED</b> 9.8W NW3000T-LED  <b>MR16 LED GU 5.3</b> 11.5W NW3000CE-LED NW3000E-LED  <b>PAR16 LED</b> 8W NW3000CA-LED
HALOGENS	<b>Remodel Housing</b> <b>MR16 GU 5.3</b> 42W IT3000LE IT3000LM	<b>New Construction Housing</b> <b>MR16 GU 5.3</b> 37W NW3000CE NW3000CM  <b>MR16 GU 5.3</b> 42W NW3000LE NW3000LM  <b>GU10</b> 50W NW3000LT
		<b>Insulated Housing</b> <b>MR16 GU 5.3</b> 20W ISMR3000E20 ISMR3000M20  <b>MR16 GU 5.3</b> 35W ISMR3000E35 ISMR3000M

Project \_\_\_\_\_

Notes \_\_\_\_\_

Fixture Type \_\_\_\_\_

Date \_\_\_\_\_



S3450D-13 (illustrated)  
(Lamp not included)



